

2.5" SATA3

Embedded Standard SSD Series



RunCore Embedded SATA3 "Elite Series" SSD utilizes high-performance SATAIII SSD controller and NAND flash, with or with no DRAM buffer to support power failure mechanism. This series SSD compliant with Serial ATA Revision 2.6/3.1 specification, compatible with 6.0Gbps, 3.0Gbps and 1.5Gbps interface rate and support Native Command Queuing (NCQ) up to 32 commands. As a standard SATA drive, it can support mainstream OS, such as Windows/Linux/Unix/Solaris/ Mac OS and so on. It offers longer SSD lifetime with lower write amplification and wear leveling factor(WLF). RunCore Elite Series is the best solution to the low power consumption, high-low temperature, moisture and shocks etc in the embedded computer\ industrial control computer\ and medical fields.



2.5" SATA3 SSD RCE-VI-T25XX-XXX

- Form Factor: Standard 2.5" 7mm or 9mm SATA SSD
- Supports SATA III standard protocol, compatible with SATA II
- Capacity:
 - pSLC: 1TB (max)
 - MLC: 2TB (max)
- Performance:
 - 4KB Random Read 60K IOPS
 - 4KB Random Write 70K IOPS
 - Sequential Write 560MB/s(max)
 - Sequential Write 450MB/s (max)
- Operating Temperature:
 - -40°C to +85°C
 - 0°C to +70°C
- Power Supply:
 - 5V, maximum power consumption 4.5W
- Physical Features:
 - Dimension 100.2mmx 69.85mmx 7mm
 - Weight ≤ 90g
- Data Security:
 - With conformal coating
 - Supports ATA command data erasure
 - Supports one-key data erasure (GPIO external pin)
 - Supports power failure protection
- Standard Compliance/ Support:
 - MIL-STD-810
 - SATA IO
 - JEDEC Endurance